



△ SPECIFICATION


Current Rating: 3A AC/DC
 Voltage Rating: 250V AC Max.
 Operation Temperature: -25°C~+85°C
 Contact Resistance: 10 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Withstanding Voltage: 1000V AC/Minute
 Contact: Brass, Tin Plated
 Insulator: PA66(UL94V-0), White
 RoHS Compliant




△




Recommended P.C.B. Layout




△ 3~12 Pin




△



△



△ 2 Pin



△

Pin	A	B
02	2.50	7.50
03	5.00	10.00
04	7.50	12.50
05	10.00	15.00
06	12.50	17.50
07	15.00	20.00
08	17.50	22.50
09	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.50

DRAWING No.

01600

SCALE

NONE

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY

WZL

REV.

A1

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X	±0.35
.XX	±0.25

UNIT
mm

A1

Modify Data

HZF

02/23/2011

A0

NEW RELEASE

HZF

08/24/2009

NO. REV.

REVISIONS

CHK

DATE