



**注記 NOTES**

1. MATES WITH : 51146 SERIES
- △ LOCKING WINDOW : ONE PLACE FOR 2 AND 3 CIRCUIT PRODUCTS AND TWO PLACES FOR MORE THAN 3 CIRCUIT PRODUCTS.
- △ MISALIGNMENT OF SOLDER TAIL AND FITTING NAIL FROM [V]  
 : UPPER DIRECTION 0.05MAX.  
 : LOWER DIRECTION 0.15MAX.  
 : OFFSET BETWEEN UPPER AND LOWER 0.1MAX. (UNDER 20 CKTS.)
- △ APPLY EVEN CIRCUIT PRODUCTS.
5. MATERIAL  
 WAFER : PPS , UL94V-0  
 PIN : PHOSPHOR BRONZE  
 0.2  
 CONTACT AREA : GOLD 0.2 MICROMETER MINIMUM  
 3.0  
 TAIL AREA : TIN 3.0 MICROMETER MINIMUM  
 1.0  
 UNDER PLATING : NICKEL 1.0 MICROMETER MINIMUM  
 FITTING NAIL : PHOSPHOR BRONZE  
 TIN 3.0 MICROMETER MINIMUM  
 UNDER PLATING : NICKEL 1.0 MICROMETER MINIMUM
6. 53780- \*\* 10 / - \*\* 18  
 THIS PRODUCT IS LEAD FREE OF 53780- \*\* 10 / - \*\* 18.
7. ELV & RoHS COMPLIANT.

16.25	22.5	38.77	36.25	42.65	53780-3070	30	
8.75	22.5	26.27	23.75	30.15	-2070	20	
7.5	20	23.77	21.25	27.65	-1870	18	
6.25	16.25	20.02	17.5	23.9	-1570	15	
5	15	18.77	16.25	22.65	-1470	14	
3.75	12.5	16.27	13.75	20.15	-1270	12	
2.5	10	13.77	11.25	17.65	-1070	10	
2.5	8.75	12.52	10	16.4	-0970	9	
1.25	7.5	11.27	8.75	15.15	-0870	8	
1.25	6.25	10.02	7.5	13.9	-0770	7	
—	5	8.77	6.25	12.65	-0670	6	
—	3.75	7.52	5	11.4	-0570	5	
—	2.5	6.27	3.75	10.15	-0470	4	
—	—	5.02	2.5	8.9	-0370	3	
—	—	3.77	1.25	7.65	53780-0270	2	
E	D	C	B	A	EMBOSSED PACKAGE	CKT.	
						エ-ダ-番号 ORDER No.	極数

<b>REVISED</b> EC NO. : J2010-1927 DRWN: SKUROSE 2010/03/25 CHYKOKASAKAMA 2010/03/26 APPR: NIKITA 2010/03/29	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE <b>MM ONLY</b>		SCALE ---	DESIGN UNITS <b>METRIC</b>	THIRD ANGLE PROJECTION
	10 UNDER	± 0.2	DRAWN BY	DATE			
	10 OVER 30 UNDER	± 0.25	T. UENO	'04/04/15			
	30 OVER	± 0.3	CHECKED BY	DATE			
	ANGULAR ± 3 °		H.Z	'04/04/15			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY	DATE				
		M. SASAO	'04/04/15	SEE CHART			
		MATERIAL NO.					
		SIZE		A3			